

Bona[®] Conditioning Pad

Technical data sheet

This unique Pad out-performs any abrasive or conditioning material used in the wood flooring industry today for abrading wood floors between finish coats. The Conditioning Pad is designed for use on waterborne finishes but works equally well on solvent-based finishes. The conforming nature of the pads makes them ideal for most wood floor finish surfaces insuring optimum bonding and the smoothest possible final coat. Conditioning Pads are used with sifaast Delta Sheets for additional abrasion to eliminate grain raise.

- Will not leave unsightly scratches
- Abrades finish surfaces thoroughly for uniform appearance and good adhesion.
- Conforms to uneven surfaces – no shiny seams or low areas.
- Will not mar or burn the finish surface.
- Cleans easily by vacuuming.
- Long wear life compared with other abrasives.
- Glides smoothly over finish surfaces.

Technical data

- Available in 16" or 20" diameters.
- 10 pads per package.

Recommended Use

- Intercoat abrasion for sealers and finishes.
- Excellent for cleaning floor prior to recoat.

Directions

This Conditioning Pad from Bona is the new standard for surface conditioning of waterborne and solvent-based sealers and finishes. It is ideal for deburring, cleaning and smoothing wood floor sealers and finishes prior to the application of additional coats. When used on waterborne sealers with sifaast Delta Sheets, a smooth surface is prepared for finish coats while controlling grain raise. Two Pads can be used under the buffer. This allows air to circulate and helps eliminate friction heat that contributes to gumming and loading of the Conditioning Pad and the Delta Sheets.

Order Information

Item#	Size/Grit	#/Case	Lbs./Case
AAS19522203	16"/320	10	4
AAS19522101	20"/320	10	4

Sanding



Bona[®]