



1191 Venture Drive
Forest, Virginia 24551-2273
Tel 434.525.5252
www.nydreeflooring.com

MATERIAL SAFETY DATA SHEET

Page 1 of 2

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: COLORFLEX II Caulking. All Colors **CAS NO.** Mixture
COMMON NAME: Caulking **DATE PREPARED:** 01.17.10
DISTRIBUTOR: Nydree Flooring, LLC **REPLACES:** 10.06.08
MANUFACTURER: Kampel Enterprises, Inc.
EMERGENCY CONTACT: 800.457.4280
TECHNICAL INFORMATION: 800.837.4971
NFPA/HMIS RATINGS: Health=1, Fire=1, Reactivity=0
DOT SHIPPING NAME: Caulking, Non-hazardous and Non-regulated.

SECTION II - INGREDIENTS/IDENTITY INFORMATION

COMPONENT (CAS NUMBER)	PEL/TLV (SOURCE)
Texanol (25265-77-4) <2% VOC CONTENT: 34 grams per liter	Not Established

This product does not contain ingredients listed by IARC, NTP, or OSHA as carcinogens or potential carcinogens.

SECTION III - PHYSICAL DATA

FREEZING POINT: 32 °F **BOILING POINT:** Approx. 212 °F
VAPOR PRESSURE: 17 mmHg @20 °C **VAPOR DENSITY:** 1:Water Vapor
SPECIFIC GRAVITY: 1.05 (Water = 1) **EVAPORATION RATE:** Less than Ether
% VOLATILE (WEIGHT): 40.7% **SOLUBILITY IN WATER:** Partial
APPEARANCE AND ODOR: Paste-like caulk with slight ammonia odor.

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT: None **FLAMMABLE LIMITS:** LEL: N/A UEL: N/A
EXTINGUISHING MEDIA: Water spray, regular foam, carbon dioxide or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: The use of self-contained breathing apparatus is recommended for firefighters. Cool exposed containers with water. Product will not burn but may splatter if temperature exceeds boiling point. Acrylic latex polymer films are capable of burning.
AUTOIGNITION TEMPERATURE: None. **HAZARDOUS PRODUCTS OF DECOMPOSITION:** Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide. Small quantities of Nitrogen Oxides may also be formed.

SECTION V – HEALTH HAZARD AND FIRST AID PROCEDURES

SKIN CONTACT: If this product comes in contact with the skin, wash with soap and water. Remove and wash contaminated clothing with soap and water before reuse. It is easier to remove caulking from clothing and skin before it dries. Obtain medical attention if irritation from contact persists. **EYE CONTACT:** Immediately flush with large quantities of water for at least 15 minutes. Seek immediate medical attention. **INHALATION:** If breathing difficulties, dizziness or light-headedness occurs, remove individual to fresh air. If breathing stops, begin artificial respiration and seek immediate medical attention. Keep person warm and quiet. **INGESTION:** If victim is conscious, administer two glasses of water. Keep victim warm and quiet. Get medical attention immediately. **MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** People with pre-existing skin and respiratory disorders (like asthma) may be more aggravated by the effects of this material

MATERIAL SAFETY DATA SHEET

SECTION VI - REACTIVITY DATA

STABILITY: This product is stable in most conditions. Use this product only as recommended by manufacturer.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

CONDITIONS TO AVOID: Avoid eye contact. Minimize skin contact, breathing of vapors, and ingestion. Keep out of the reach of children. Do not take internally.

SECTION VII - USER PROTECTION INFORMATION

VENTILATION: May be needed if used indoors in areas with poor general ventilation. General mechanical ventilation is recommended when the product is used indoors.

RESPIRATORY PROTECTION: Not normally required. If uncertain of vapor concentration, use a National Institute of Occupational Safety and Health approved respirator.

PROTECTIVE CLOTHING: Wear rubber gloves, rubber apron, and impervious boots.

EYE PROTECTION: Wear goggles or safety glasses as needed to prevent eye entry.

SECTION VIII - SPILL OR LEAK PROCEDURES

SPILL OR LEAK PROCEDURES: Provide adequate ventilation. Transfer material to containers for recovery or disposal with a shovel. Keep material out of sewers and open bodies of water. Dispose of product in accordance with applicable local, country, state and federal regulations.

LARGE SPILL: Isolate from oxidizers. Contact approved Haz Mat remedial agency for disposal.

TRANSFER METHOD: Ground containers to prevent static spark. Prevent vapor accumulation; close containers, ventilate area.

WAREHOUSING: Store in plastic or lined containers, tightly sealed. Keep containers cool, dry and away from sources of ignition. Keep from freezing. Keep product containers closed when not in use.

DISPOSAL: Observe Federal, State, and local regulations. Recycle spent wash water in approved equipment. Contact RCRA approved Hazardous Waster Recycling/Disposal facility.

SECTION IX - MISCELLANEOUS

HANDLING: For industry use only. *KEEP OUT OF REACH OF CHILDREN*

STORAGE: Protect from freezing and excessive heat. Keep containers closed and upright.

EFFECTS OF CHRONIC OVEREXPOSURE: Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

The information and data herein are believed to be accurate and have been compiled from sources believed to be accurate. It is offered for your consideration, investigation, and verification. NYDREE Flooring, LLC makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. NYDREE Flooring, LLC will not be liable for claims relating to any party's use or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.