



1191 Venture Drive
Forest, Virginia 24551-2273
Tel 434.525.5252
www.nydreeflooring.com

MATERIAL SAFETY DATA SHEET

Page 1 of 2

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: Nydree Flooring Dust Mop Treatment	CAS NUMBER: None - Mixture
COMMON NAME: Cleaning Compound	CHEMICAL NAME: None
DISTRIBUTOR: Nydree Flooring, LLC	
EMERGENCY CONTACT: 800.424.9300	DATE PREPARED: 01.17.10
TECHNICAL INFORMATION: 800.682.5698	REPLACES: 06.20.08
NFPA/HMIS RATINGS: Health=1, Fire=1, Reactivity=0	
DOT SHIPPING NAME: Petroleum Oil, Not Regulated	

SECTION II - INGREDIENTS/IDENTITY INFORMATION

COMPONENT (CAS NUMBER)	PEL/TLV (SOURCE)
Petroleum Distillate (64741-88-4) & (64741-89-5) Petroleum Naphtha (64742-88-7) OSHA REG. 29 CFR 1910.1200: None. SARA TITLE III SECTION 313: None.	5 mg/M ³ (OSHA, ACGIH) 100 ppm (OSHA, ACGIH)* *Not established for this CAS#, use Stoddard Solvent (8052-41-3) for PEL/TLV

SECTION III - PHYSICAL DATA

BOILING POINT: 305 °F	VAPOR DENSITY: 4.7 (Air = 1.0)
VAPOR PRESSURE: 6.6 mmHg	ph: Not Applicable.
SPECIFIC GRAVITY: 0.86 (Water = 1)	SOLUBILITY IN WATER: Negligible
DENSITY: 7.16 lbs./gal	% VOLATILE (VOLUME): 6%
V.O.C.'s: Less than 7%.	EVAPORATION RATE: Slower than 1 (Ethyl Ether =1)
APPEARANCE AND ODOR: Slightly yellow-transparent liquid, pleasant odor.	

SECTION IV - FIRE AND EXPLOSION DATA

AUTOIGNITION TEMPERATURE: 243 °C **FLASH POINT:** Greater than 225 °F (P.M.C.C.)
EXTINGUISHING MEDIA: Water spray, regular foam, or carbon dioxide.
EXPLOSIVE LIMITS IN AIR: Not Established.
SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be helpful in minimizing vapor and cooling containers exposed to heat and flame. Use self-contained breathing apparatus (SCBA) and turn out gear in a sustained fire. Wear structural firefighters protective clothing.
UNUSUAL FIRE AND EXPLOSION HAZARD: Can be made to burn (flash point 225 °F)
Incomplete combustion can yield carbon monoxide and various hydrocarbons.

SECTION V - HEALTH HAZARDS

SKIN AND EYE CONTACT: Direct contact with skin may cause irritation on sensitive skin. Open cuts and sores may be irritated by contact. Direct contact with eyes may cause irritation.
INHALATION: Breathing vapors may cause slight irritation of the nose, throat, and respiratory tract. Prolonged overexposure may cause headache, dizziness, nausea or unconsciousness.
INGESTION: Excessive quantities may cause irritation of the digestive tract.
CHRONIC EFFECTS: No known effects. No components in this mixture is listed by IARC, NTP, NIOSHA, or ACGIH as a carcinogen.

MATERIAL SAFETY DATA SHEET

SECTION VI - REACTIVITY DATA

STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in air produces carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Strong oxidizing agents, strong acids or bases and selected amines.

CONDITIONS TO AVOID: None known.

SECTION VII - USER PROTECTION INFORMATION

RESPIRATORY PROTECTION: Not normally required. **VENTILATION:** USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Provide adequate general and/or local exhaust ventilation to maintain healthful working conditions. At least 10 air changes/hour is recommended. **EYE PROTECTION:** Wear goggles or safety glasses as needed to avoid splashing in eyes. **PROTECTIVE CLOTHING:** Normal use – Protective clothing such as uniforms, coveralls and PVC, neoprene, nitrile, viton or polyurethane gloves. **OTHER:** Wash thoroughly after handling; wash contaminated clothing before reuse.

SECTION VIII - EMERGENCY AND FIRST AID PROCEDURES

EYES: If irritation or redness develops, move victim away from source of exposure and into fresh air. Flush eyes with clean water for at least 15 minutes. If symptoms persist, seek medical attention.

SKIN: First aid is not normally required, however, it is good practice to wash any chemical from the skin with soap and water.

INHALATION: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. Obtain medical attention if fresh air does not relieve irritation.

INGESTION: If swallowed do not induce vomiting. Call a physician immediately.

SECTION IX - SPILL OR LEAK PROCEDURES

LARGE & SMALL SPILLS: Remove all sources of ignition. Avoid breathing vapors or spray mist. Ventilate area and remove with inert absorbent. Do not pick up solution with automatic scrubber or wet pick-up vacuum. **WASTE DISPOSAL METHOD:** Dispose material and absorbent according to federal, state, and local regulations. Do not dispose of in storm drains and waterways

SECTION X - MISCELLANEOUS

HANDLING: For industry use only. *KEEP OUT OF REACH OF CHILDREN*

STORAGE: Protect from freezing and excessive heat. Keep containers closed and upright.

EMPTY CONTAINERS: Do not transfer material into unlabeled containers. Do not reuse empty containers.

The information and data herein are believed to be accurate and have been compiled from sources believed to be accurate. It is offered for your consideration, investigation, and verification. NYDREE Flooring, LLC makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. NYDREE Flooring, LLC will not be liable for claims relating to any party's use or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.