



UP-28-0VOC Adhesive Bond Limited Warranty OVR-8 Moisture Protection Limited Warranty

UP-28-0VOC Adhesive Bond Limited Warranty

Nydree Flooring warrants that UP-28-0VOC adhesive is free from manufacturing defects and will bond all Nydree Engineered Hardwood Flooring to those substrates common to hardwood flooring installation for a period of five (5) years provided the moisture levels do not equal or exceed 8 lbs./1000 sf /24 hours or do to equal or exceed 85% insitu relative humidity, certified by the required number of Calcium Chloride Tests (ASTM F1869) or required number of insitu Relative Humidity Tests (ASTM F2170). The UP-28-0VOC adhesive must be used in strict accordance with the manufacturer's installation instructions. Failure to follow these specific installation instructions completely will void this warranty.

OVR-8 Moisture Protection Limited Warranty

Nydree Flooring warrants that OVR-8 Self Leveling Moisture Retarder is free from manufacturing defects. Nydree Flooring warrants that UP-28-0VOC, when used in conjunction with OVR-8 Self Leveling Moisture Retarder, will bond and will protect all Nydree Flooring, designed and recommended in writing by the wood flooring manufacturer for glue-down, against moisture damage through the sub-floor only (e.g.: cupping, end lifting, warping) for a period of five (5) years.

These warranties are contingent upon the following:

- The evaluation of a potential claim by a Nydree Flooring representative in advance of any replacement work, submittal of wood flooring manufacturer's product warranty, and a copy of the original materials and installation invoice(s). Any repairs conducted prior to evaluation will void all warranties.
- The OVR-8 and UP-28-0VOC Adhesive are used in accordance with Nydree Flooring's most recent published literature.
- The wood flooring must be installed in accordance with the wood flooring manufacturer's most recent published literature pertaining to UP-28-0VOC glue down installations, including but not limited to, wood flooring acclimation, expansion space, jobsite temperature, relative humidity and air flow requirements.
- The installation must be maintained in accordance with the wood flooring manufacturer's recommendations including, but not limited to, temperature, relative humidity, and proper maintenance.
- This warranty does not cover damage (e.g.: cupping, end lifting, warping) due to flooding, hydrostatic head, puddling, improper maintenance, low/excessive relative humidity and/or temperature, or any issues not related to excessive moisture proven to be coming through the OVR-8 membrane.
- This warranty is to the original purchaser and is non-transferable. Nydree Flooring will repair or replace the affected flooring one time only.

In the event of a valid claim under this warranty, Nydree Flooring will pay to repair or replace on a square foot basis the portion(s) of the installation that is proven to be defective. This payment is to include all reasonable materials and labor only. Nydree Flooring is not responsible for workmanship not in accordance with Nydree Flooring's most recent published literature, abuse, misuse, or losses due to delays or any other consequential damages.

The UP-28-0VOC Adhesive Bond Limited Warranty and OVR-8 Moisture Protection Limited Warranty is sellers only warranty. Seller makes no other express warranties, and seller makes no implied warranties of merchantability nor of fitness for a particular purpose. In no event shall seller be liable for incidental and consequential damages caused by breach of warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.