



1191 Venture Drive
Forest, Virginia 24551-2273
Tel 434.525.5252
www.nydreeflooring.com

MATERIAL SAFETY DATA SHEET

Page 1 of 2

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: Nydree Flooring Spray Whitener Cleaner **CAS NUMBER:** None - Mixture
COMMON NAME: Cleaning Compound **CHEMICAL NAME:** None
DISTRIBUTOR: Nydree Flooring, LLC
EMERGENCY CONTACT: 800.682.5698 **DATE PREPARED:** 01.17.10
TECHNICAL INFORMATION: 800.682.5698 **REPLACES:** 08.11.09
NFPA/HMIS RATINGS: Health=1, Fire=0, Reactivity=0
DOT SHIPPING NAME: Compound Cleaning Liquid, Not Regulated

SECTION II - HAZARDOUS INGREDIENTS

| COMPONENT (CAS NUMBER) | EXPOSURE LIMITS - (SOURCE) |
|--|---------------------------------------|
| Glycol Ether EB (111-76-2) 1-2% by weight. OSHA REG. 29 CFR 1910.1200: Glycol Ether EB. SARA TITLE III SECTION 313: Glycol Ether EB. | 50 ppm (OSHA PEL), 20 ppm (ACGIH TWA) |

SECTION III - PHYSICAL DATA

BOILING POINT: 212 °F **VAPOR DENSITY:** Not Available.
VAPOR PRESSURE: Same as water **ph:** 8.8 ± 0.1
SPECIFIC GRAVITY: 1.0 (Water = 1) **SOLUBILITY IN WATER:** Miscible
DENSITY: 8.33 lbs./gal **V.O.C.'s:** 20 grams/Litre
EVAPORATION RATE: 1.00 (Water =1)
APPEARANCE AND ODOR: White aqueous liquid with mild detergent odor.

SECTION IV - FIRE AND EXPLOSION DATA

AUTOIGNITION TEMPERATURE: None known. **FLASH POINT:** None known.
EXTINGUISHING MEDIA: Water, dry chemical, foam, or carbon dioxide.
SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be helpful in minimizing vapor and cooling containers exposed to heat and flame. Use self-contained breathing apparatus (SCBA) and turn out gear in a sustained fire.
UNUSUAL FIRE AND EXPLOSION HAZARD: Closed containers may explode due to build up of steam pressure when exposed to extreme heat.

SECTION V - HEALTH HAZARDS

SKIN AND EYE CONTACT: Direct contact with skin may cause irritation on sensitive skin. Direct contact with eyes may cause irritation. **INHALATION:** Breathing vapors may cause slight irritation of the nose, throat, and respiratory tract. Excessive and prolonged exposure may cause headaches and mucus membrane irritation.
INGESTION: Excessive quantities may cause irritation of the digestive tract.
SKIN ABSORPTION: Not likely to cause injury with normal handling procedures. Excessive and prolonged exposure may be harmful.
CHRONIC EFFECTS: No known effects. None of the components in this mixture is listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.

MATERIAL SAFETY DATA SHEET**SECTION VI - REACTIVITY DATA**

STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield carbon monoxide and/or carbon dioxide, hydrocarbon, and oxides of nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Avoid strong oxidizers.

CONDITIONS TO AVOID: Temperature extremes. Keep from freezing.

SECTION VII - USER PROTECTION INFORMATION

VENTILATION: Provide adequate general and/or local exhaust ventilation to maintain healthful working conditions.

RESPIRATORY PROTECTION: None needed when provided with general ventilation.

PROTECTIVE CLOTHING: Wear vinyl or rubber gloves, coveralls, etc. as needed to minimize skin contact.

EYE PROTECTION: Wear goggles or safety glasses as needed to prevent splashing in eyes.

OTHER: Wash thoroughly after handling. Wash contaminated clothing before reuse.

SECTION VIII - EMERGENCY AND FIRST AID PROCEDURES

EYES: If irritation or redness develops, move victim away from source of exposure and into fresh air. Flush eyes with clean water for at least 15 minutes. If symptoms persist, seek medical attention.

SKIN: First aid is not normally required, however, it is good practice to wash any chemical from the skin. Apply moisturizing skin cream.

INHALATION: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. Treat symptomatically and call a physician.

INGESTION: Do not induce vomiting only if victim is conscious. Call a physician immediately.

SECTION IX - SPILL OR LEAK PROCEDURES

See Section VII for protection information. Collect spilled material in suitable retaining areas or containers for salvage or disposal. Material may be absorbed into an appropriate absorbent. Dispose material and absorbent according to federal, state, and local regulations.

SECTION X - MISCELLANEOUS

HANDLING: For industry use only. Keep out of reach of children.

STORAGE: Do not store above 120 °F. Keep containers closed and upright. Keep from freezing.

EMPTY CONTAINERS: Do not reuse empty containers.

The information and data herein are believed to be accurate and have been compiled from sources believed to be accurate. It is offered for your consideration, investigation, and verification. NYDREE Flooring, LLC makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. NYDREE Flooring, LLC will not be liable for claims relating to any party's use or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.