



1191 Venture Drive
Forest, Virginia 24551-2273
Tel 434.525.5252
www.nydreeflooring.com

MATERIAL SAFETY DATA SHEET

Page 1 of 2

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: Nydree Group Touch Up Polyurethane (Satin) **CAS NUMBER:** None
COMMON NAME: Water-Based Polyurethane **CHEMICAL NAME:** None
DISTRIBUTOR: Nydree Flooring, LLC
EMERGENCY CONTACT: 800.682.5698 **DATE PREPARED:** 01.17.10
TECHNICAL INFORMATION: 800.682.5698 **REPLACES:** 08.12.09
HMIS RATINGS: Health=1, Flammability=1 Reactivity=0 Protection: B
DOT SHIPPING NAME: Paint, Not Regulated

SECTION II - INGREDIENTS/IDENTITY INFORMATION

COMPONENT (CAS NUMBER)	PEL-TWA EXPOSURE LIMIT
Dipropylene Glycol Monomethyl Ether (34590-94-8)	100 PPM (OSHA)
N-Methyl-2-Pyrrolidone (872-50-4)	100 PPM (OSHA)
Dimethylethanolamine (108-01-0)	N.E.

SECTION III - PHYSICAL DATA

BOILING RANGE: 273 - 379 °F **VAPOR DENSITY:** Heavier than Air.
SOLUBILITY IN WATER: Miscible **EVAPORATION RATE:** Faster than Butyl Acetate.
SPECIFIC GRAVITY: 1.0503 (Water = 1) **DENSITY:** 8.748 lbs./gal
APPEARANCE AND ODOR: Ivory, milky liquid with slightly sweet odor.

SECTION IV - FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION: Non-Flammable. **FLASH POINT:** Over 350°F(177°C) SFCC
FLAMMABLE LIMITS: None **EXTINGUISHING MEDIA:** Dry chemical, foam, water fog, or carbon dioxide. **SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be helpful in minimizing vapor and cooling containers exposed to heat and flame. Use self contained breathing apparatus (SCBA) in a sustained fire. **UNUSUAL FIRE AND EXPLOSION HAZARD:** Closed containers exposed to extreme heat may rupture due to pressure build up.

SECTION V - HEALTH HAZARDS AND FIRST AID PROCEDURES

EYE CONTACT: May cause irritation, redness and tearing. In case of contact, flush immediately with large amounts of water for 15 minutes and obtain medical attention. **SKIN CONTACT:** Prolonged or repeated contact may cause drying of skin. In case of contact, wash area with soap and water. Apply moisturizing skin cream. **INHALATION:** Excessive inhalation of vapors may cause dizziness, nausea and possible headache. If affected by inhalation, remove to fresh air. **INGESTION:** May cause gastrointestinal irritation and nausea. If swallowed, drink 1 or 2 glasses of water to dilute. Get medical attention. **CHRONIC EFFECTS:** None of the components in this product are listed by IARC, NTP, or OSHA, as a carcinogen, teratogen, mutagen, or as having toxic reproductive effects. **REGULATORY DATA:** This product contains the following chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40CFR372: N-Methyl-2-Pyrrolidone(872-50-4) 6.1%.
WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm: N-Methyl-2-Pyrrolidone (872-50-4) and Hydrazine (302-01-2).

MATERIAL SAFETY DATA SHEET**SECTION VI - REACTIVITY DATA**

STABILITY: Stable. **HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.
REACTIVITY WITH WATER: Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield carbon monoxide and/or carbon dioxide, and oxides of nitrogen.
CONDITIONS TO AVOID: Do not store in a high temperature (above 120 °F or 49 °C) environment. Keep from freezing.
INCOMPATIBILITY: Strong Oxidizers.

SECTION VII - USER PROTECTION INFORMATION

VENTILATION: Provide adequate general and/or local exhaust ventilation to maintain exposure level below TLV.
RESPIRATORY PROTECTION: None needed when provided with general ventilation.
PROTECTIVE GLOVES: Wear rubber gloves.
EYE PROTECTION: Wear goggles or safety glasses as needed to prevent splashing in eyes. Have an eyewash station available. **OTHER PROTECTIVE EQUIPMENT:** Wear impervious clothing to avoid repeated or prolonged skin contact. **HYGIENIC PRACTICES:** Wash hands with soap and water before eating or using rest rooms.

SECTION VIII – SPILL OR LEAK PROCEDURES

IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Remove with inert absorbent.
WASTE DISPOSAL: Dispose of contaminated absorbent, container and unused contents in accordance with local, state/provincial and federal regulations.
SHIPPING INFORMATION: Not regulated as a DOT hazardous material.

SECTION X - MISCELLANEOUS

Do not transfer contents to bottles or other unlabeled containers.

*****KEEP OUT OF THE REACH OF CHILDREN*****

The information and data herein are believed to be accurate and have been compiled from sources believed to be accurate. It is offered for your consideration, investigation, and verification. Nydree Flooring, LLC makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. Nydree Flooring, LLC will not be liable for claims relating to any party's use or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.