



**All Nydree Engineered Flooring Products
Pedestrian UV-Cured Finish
Tykote® / StreetShoe® 275 Dustless Recoating System
Pedestrian Recoating and Preventative Sealing**

Worn or Lightly Scratched Finish (The Pedestrian finish is not worn through to the wood)

In this case it is not necessary to remove the factory-applied Pedestrian coating to refinish a Nydree Flooring installation. Basic's TyKote / StreetShoe 275 Dustless Recoating System has been tested and approved for use on all Nydree Flooring Products, (PermaGrain and Gammapar Flooring finished with Pedestrian UV-Cured Finish). Basic's TyKote / StreetShoe 275 Dustless Recoating System is designed to fill in most light surface scratches (light scratches in the existing finish only), cover and renew most traffic patterns and provide a beautiful, just-finished appearance. Outlined below is the general TyKote / StreetShoe 275 procedure. A complete procedure is available by contacting Basic Coatings Customer Service @ 800.441.1934 or the web @ <http://www.basiccoatings.com/Training/Pages/Online%20Library.aspx>. Follow all manufacturers' instructions.

Newly Installed Nydree Flooring

When Nydree Flooring is used in an environment where there is potential for spills and frequent spot cleaning (restaurants / bars / food service areas) it is recommended that the flooring be completely sealed. The TyKote / StreetShoe 275 Dustless Recoating System can be used on newly installed Nydree Flooring to seal all of the plank edges. Follow the instructions below, but skip steps #1 and #2, for newly installed flooring. *It is important to note that on newly installed flooring, the UP-28-0VOC installation adhesive must cure for at least 48 hours prior to using the TyKote / StreetShoe 275 System.*

Damaged Finish (Spots of the Pedestrian finish are completely worn away or heavy scratches/gouges)

See Complete Pedestrian/Old Finish Removal and Recoating Procedure under Maintenance Instructions on the Nydree Flooring website.

TYKOTE / STREETSHOE 275 RECOATING PROCEDURE – FOLLOW MANUFACTURER'S INSTRUCTIONS

IMPORTANT INFORMATION – DO NOT USE the Basic TyKote / StreetShoe 275 Dustless Recoating System over Pedestrian finish that has paste wax, acrylic floor polish or acrylic wax on its surface.

1. Test for paste wax, acrylic floor polishes and acrylic wax.
2. Repair scratches that go through the existing finish to the wood surface.
3. Sweep and vacuum the floor to remove any loose dirt.
4. Clean the floor with properly diluted Basic Intensive Floor Treatment (IFT). Repeat if required.
5. Rinse the floor by damp mopping with clean water until the rinse water remains clear after use.
6. Clean the floor using properly diluted Basic Squeaky™ Cleaner.
7. Apply TyKote to the floor in a **very thin layer** using a clean microfiber mop. Allow to dry one hour with good ventilation. Tykote should be dry to the touch. Do not exceed six hours before applying topcoat or the TyKote may lose effectiveness.
8. Immediately apply StreetShoe 275 in the desired sheen level. StreetShoe 275 Satin matches the original factory finish of Nydree (PermaGrain and Gammapar) flooring with the following exceptions: *List of factory finished flooring that matches StreetShoe 275 Super Matte.*
Nydree Flooring Vanilla, Bella Luna, Harvest Wheat, Essences de Rosa, Ice and Centennial. Timeless Series 4 Alabaster Sand, Vanilla and November Sky. Jefferson Collection III Stonewall, Winter Whisper, Essences de Rosa, Cerise Ice, Bella Luna and Harvest Wheat.
After the initial coat of StreetShoe 275 is dry (approximately 3-4 hours) a second coat may be applied. However, the second coat must be applied within 24 hours of the initial finish coat. StreetShoe 275 is also offered in semi-gloss and gloss finishes, if desired.
9. Twenty-four hours after applying the last coat of StreetShoe 275, furniture may be replaced and the floor can be returned to normal traffic.
10. The new finish can be maintained with Nydree Urethane Finish Cleaner and Nydree Dust Mop Treatment two weeks after the StreetShoe 275 has been applied. Rugs can also be replaced at this time.

Any of the TyKote / StreetShoe 275 System products can be purchased through Nydree Flooring Customer Service by calling 800.682.5698.

StreetShoe® and TyKote® are registered trademarks of Basic Coatings
© 2010 Nydree Flooring, LLC

07/10